





203026
DCCK 30 M 20 AIK
Inductive proximity sensor

- Analog voltage output
- Analog current output
- Highly flexible cable
- Integrated amplifier
- Starting pulse suppression



1) Width over flats 36 mm

BK: black

BN: brown

BU: blue

WH: white

Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	10 ... 30 V DC
Internal power consumption	10 mA
Insulation voltage endurance	According to IEC 60947-5-2 (7.2.3.1)
Installation type	quasi-flush
Thread	M30 x 1.5
Housing length	35 mm
Housing material	Brass (CuZn, nickel-plated)
Material of sensor probe	PBTP (Crastin)
Tightening torque	70 Nm
Protection class	III, operation on protective low voltage
Operating principle	inductive
Evaluation	analog
Design	Thread
Characteristics	extremely high operating distance
Product series	INA Analog
Analog output	0 ... 5 V, 1 ... 5 mA
Switching distance (SN)	0 ... 20 mm
Standardized measuring plate	60 x 60 x 1 mm
Switching frequency	200 Hz
Ambient temperature during operation	-25 ... +70 °C
Protection type	IP 67
Connection	Cable, 2.0 m (flying leads)

More information / accessories

<https://www.di-soric.com/203026>