



207261
LT 21 K 300 P3
Retroreflective diffuse sensor

- Long ranges with a small design
- High resolution
- Visible red light with small light spot
- Sensitivity is adjustable
- LED switching status display



1) LED STABILITY
 2) LED OPERATION
 3) sensitivity

4) Receiver
 5) Transmitter

BK: black BN: brown BU: blue PK: pink

Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10.8 ... 26.4 V DC
No-load current (max.)	15 mA
Insulation voltage endurance	1000 V
Housing dimensions	22 x 13 x 8.5 mm
Housing length	13 mm
Housing height	22 mm
Housing width	8.5 mm
Housing material	Plastic
Material	Acrylic (Window)
Protection class	III, operation on protective low voltage
Operating principle	Retroreflective diffuse sensor
Evaluation	digital
Design	Cuboid design
Switching output	pnp, 50 mA, NO/NC
Light source	Laser
Laser class	1 (IEC 60825-1)
Color	red
Wavelength	655 nm
Modulation	Clocked
Ambient light immunity	3 kLx



207261
LT 21 K 300 P3
Retroreflective diffuse sensor

Technical data (typ.)	+20°C, 24 V DC
Scanning range	45 ... 300 mm
Resolution	Ø 1.0 mm (with operating range 300 mm)
Smallest detectable object	Ø 0.01 mm (Gold wire)
Switching hysteresis (max.)	20 %
Sensitivity adjustment	Potentiometer
Switching frequency	1000 Hz
Response time	0.50 ms
Ambient temperature during operation	-10 ... +55 °C
Vibration/shock resistance	10 ... 500 Hz / 1.5 mm / 10 G
Protection type	IP 67
Connection	Cable, 2.0 m, 4-pin (flying leads)
Connection cable	TK ... /4

More information / accessories	https://www.di-soric.com/207261
---------------------------------------	--